R-3201
ALKYLATOR

DIMENSION: , 4700.0 mm ID X 48400.0 mm T-T
DESIGN P AND T: 26.97 kg/cm^2g AND 300.0 C
MINIMUM P AT T: /FV
TYPE AND MATL OF TRAY: - 410 S.S.
MATERIAL OF CONSTRUCTION: CS
INSULATION TYPE AND THICK: HC - 64.0 mm (SHELL)
- (HEAD)

EXTERNAL AT 300.0 C

PSET=28.00 kg/cm^2g

32-P1-EF-014 | 10999 — FC-32030
32-P1-EF-005 | 1541 — FC-32013
32-P1-EF-012 | 11289 — PY-32900
32-P1-EF-014 | 1455 — PV-32002B
32-P1-EF-014 | 9089 — PV-32002A
32-P1-EF-006 | 1403 — FC-32021

HC 32042 · PY 32002 · PC 32002C · PC 32002B · PC 32002A · FOR START UP
PI 32007X · PI 32007Y · PI 32007Z · ESD-5 32102 · PT 32007X · PT 32007Y · PT 32007Z · 2OO3 · DETAIL "O2"
PT 32002 · DETAIL "O2"
PRD 32001 · PRD 32041 · 8T10 · NBZ3 · EBZ · CSO · 16"x8" · 24"x10" · 16" CSC
SLOPE 1000.0 mm/500.0 m
HAP V-32030-24"-EBZ-HC38.0 mm-ET → FLARE 3230 | 32-P1-EF-112
HAP V-32107-24"-EBZ-HC38.0 mm-ET → FLARE 13872 | 32-P1-EF-112
TUI 32301 · TUT 32301 · TI 32012 · TW 32012 · RTD · 2" · MIN · 8" · 1"
HAP P-32004-24"-NBZ3-HC51.0 mm-NT → ALKYLATOR EFFLUENT 1336 | 32-P1-EF-005 | E-3202
HAP P-32528-16"-NBZ3-HC51.0 mm-ET
XB2A NBZ3 · (DO NOT POCKET)
HAP P-32008-12"-NBZ3-HC38.0 mm-NT → ALKYLATOR REFLUX 32-P1-EF-006 | 1215 | P-3202A/B & P-3203A/B
HAP P-32531-10"-NBZ3-HC38.0 mm-NT
HAP P-32102-6"-NBZ3-HC38.0 mm-NT
SIPHON BREAKER · NNF · (DO NOT POCKET)
PDI 32001 · PDT 32001 · 0.75" NPT · PACKING · 30" MW · 2"x1" · 2" · 24" · 12" · 10"x8" · 8"
PI 32003 · PT 32003 · VC-31 · 0.75" NPT
PACKING
Trim: TR-32001-NBZ3 HAP-HC
HHLL=27090.0 mm
HLL=26590.0 mm
NLL=25590.0 mm
LLL=22890.0 mm
LLLL=22390.0 mm
TW 32003 · TUT 32300 · TUI 32300 · TI 32003 · LT 32003X · LT 32003Z · ESD-5 32101 · 2OO3 · D/P · DETAIL "O2" · RTD
LI 32003X · LI 32003Y · LI 32003Z
HAP P-32020-10"-XD1JA-HC51.0 mm-NT → FINISHING REACTOR BLOWDOWN 32-P1-EF-016 | 1328 | R-3203
2 PHASE · FREE DRAINING
NH-32001-8"-N1-HC38.0 mm-NT → STEAM / NITROGEN PURGE 32-P1-EF-109 | 1251 | E-3226
NNF · SHUT-DOWN PURGING
ALKYLATOR OVERHEAD PRESSURE CONTROL
OPEN · CLOSED · 0 · 100% · PV-32013 · PV-32002B · PC-32002C OUTPUT
FC 32890 · FY 32890 · FT 32890 · FV 32890 · FE 32890 · 4"x2" · 1"
HAP P-32261-4"-XB2A-N -NT → C2 FEED BYPASS 32-P1-EF-002 | 10846 | ETHYLENE FEED
IPL · LC 32002 · PDI 32005 · PY 32005 · LT 32002 · LG 32002 · MAG · 3" · EB/SM · DC-31
TW 32005 · TI 32005 · TUT 32300 · TW 32004 · TW 32006 · TW 32007 · TW 32009 · TW 32008 · TI 32004 · TI 32006 · TI 32007 · TI 32009 · TI 32008 · TI 32010 · TI 32011
BED 4 · BED 3 · BED 2 · BED 1 · SPARGER · SPARGER. · MIN · MIN TYP · MW · RTD
HAP P-32205-12"-NBZ3-N -NT
HAP P-32204-12"-NBZ3-N -NT
HAP P-32203-12"-NBZ3-N -NT
HAP P-32202-12"-NBZ3-N -NT
VOC P-32001-12"-XB2A-N -NT → ETHYLENE 32-P1-EF-002 | 1409 | FV-32005
VOC P-32001-12"-XB2A-N -NT → ETHYLENE 32-P1-EF-002 | 1424 | FV-32007
ETHYLENE 1711 | 32-P1-EF-002 | FV-32006
ETHYLENE 1712 | 32-P1-EF-002 | FV-32008
FY 32004 · FFI 32004 · FC 32002 · FE 32002A · FT 32002 · FT 32034Y · FT 32034Z · FY 32002 · FV 32002 · FT 32034X · FE 32002B · FC 18" · FI 32034X · FI 32034Y · FI 32034Z
ACTUAL ETHYLENE FLOW RATE 32-P1-EF-002 | 1399 | FY-32003A
CWR 5587 | 33-P1-EF-553 · CWR-32027-0.75"-A-N -NT
HAP P-32307-0.75"-NBZ3-HC38.0 mm-ET
32-P1-EF-018 | 1560 | SC-3-3208
CWS 5588 | 33-P1-EF-553 · CWS-32027-0.75"-A-N -NT
PI 32004 · PT 32004 · 1"x0.75" · 1" · UC
DH-32116-2"-E-N -NT → WASTEWATER 4843 | 33-P1-EF-534 | EB/SM SEWER
HAP P-32041-20"-NBZ3-HC51.0 mm-NT
TRANSALKYLATOR EFFLUENT 1367 | 32-P1-EF-010 | R-3202
HAP P-32036-8"-XD1JA-HC51.0 mm-NT
MD TRAYS 10 · 9 · 8 · 1
HHLL = 5650MM
HLL = 5150MM
NLL = 3650MM
LLL = 900MM
LLLL = 400MM
common blind
HAP P-32201-12"-NBZ3-N -NT
HAP P-32534-12"-NBZ3-HC51.0 mm-NT
HAP P-32040-18"-NBZ3-HC64.0 mm-NT
XD1JA · NBZ3 · 12"x8" · 10"x8"
PDI 32006 · PDT 32006 · TC 32002 · TT 32002
TI 32207 · TUT 32300 · TW 32207 · TW 32002 · TI 32116 · TUT 32300 · TW 32116 · LT 32032X · D/P · DETAIL "O1"
T.L=10500MM · DC-31 · EB/SM · 2OO2 · ESD-5 32102
VC-31 · LT 32032Y · LT 32001 · LG 32001 · LC 32001 · IPL · LI 32032Y · LI 32032X
HAP P-32042-4"-XD1JA-PP38.0 mm-NT → FINISHING REACTOR VENT 32-P1-EF-016 | 1397 | R-3203
VOC P-32001-12"-XB2A-N -NT → ETHYLENE 32-P1-EF-002 | 1396
HAP P-32155-24"-NBZ3-HC64.0 mm-NT → ALKYLATOR BTMS 32-P1-EF-003 | 1377 | F-3201
2 PHASE · SLOPE 1000.0 mm/100.0 m
32-P1-EF-004 | 1245 | FC-32010
1404 | 32-P1-EF-018 | FC-32001
First line break
HAP P-32027-10"-NBZ3-HC64.0 mm-NT → ALKYLATOR BTMS 1189 | 32-P1-EF-018 | C-3201
ALKYLATOR BTMS 32-P1-EF-003 | 1366 | P-3201A/B
HAP P-32037-20"-NBZ3-HC64.0 mm-NT

13. DELETE.
14. DURING PG ETHYLENE MODE ALKYLATOR PRESSURE WILL BE CONTROLLED BY PC-32030
15. HIGH LEVEL ALARMS ON LI32003X/Y/Z ARE IPL ALARMS

NOTES:
1. TOP OF SEAL LOOP TO BE AT LEAST 5M ABOVE HLL IN R-3201.
2. TO MEASURE THE LIQUID TEMPERATURE FROM TRAY TO DOWNCOMER.
3. SYMMETRICAL PIPING.
4. COMMON ALARM OF EACH HEAT TRACE LOCAL PANEL IS PROVIDED ON DCS.
5. FFI-32004 INDICATES ALKYLATE TOTAL ETHYLENE FLOW RATIO IN WEIGHT.
6. CONTROL VALVE STATION TO BE LOCATED AT GRADE & AT BOTTOM OF SEAL LOOP.
7. HEIGHT BASED ON PUMP P-3201A/B NPSH REQUIREMENTS.
8. DELETED.
9. VALVE TO BE AT MINIMUM DISTANCE FROM SC.
10. ROUTE LEVEL BRIDLE DRAINS TO EB/SM SEWER AND VENT TO FLARE.
11. MAINTENANCE VALVE FOR STEAMING COLUMN.
12. DOWNSTREAM OF SPECTACLE BLIND SHALL BE SLOPED.

REV.	DATE	DESCRIPTION	DRAWN	CHKD.	APPD.	REFERENCE DRAWING
10	14.Apr.-2021	REVISED AS PER MOC JCP-P-9035	MRH	CSK	HBK	FOR NEW JCP LEGEND AND SYMBOLS SEE DRAWINGS:
09	02.Jul.-2015	REVISED FOR IPL IDENTIFICATION	PTB	JRB	KMN	JCP-00-P1-EF-001 THRU JCP-00-P1-EF-039
08	10.Jul.-2014	AS PER MOC JCP-P-2222	MRH	AM	KMN	FOR EXISTING SCP LEGEND AND SYMBOLS SEE DRAWINGS:
07	07.May.-2014	REVISED AS PER MOC JCP-P-P-896	HER	S.K	KMN	JCP-00-D-00-00001 THRU JCP-00-D-00-00023
06	20.Feb.-2014	REVISED AS PER MOC	AM	DF		FOR EXISTING PORT LEGEND AND SYMBOLS SEE DRAWINGS:
11	01.Sep.-2022	REVISED AS PER MOC-21-5695	MRH	CSK	GMM	JCP-00-D-00-00001P THRU JCP-00-D-00-00012P

CONFIDENTIAL INFORMATION - REPRODUCTION AND USE PROHIBITED EXCEPT IN ACCORDANCE WITH COMPANY
EPC CONTR: JGC
JCP
MANAGING CONTRACTOR: PARSONS E&C

	INITIAL	DATE
DRAWN	PEC	04.Feb.-2003
CHECKED		
CONTRACTOR APPROVAL	RRC	
	JM	
JCP APPROVAL	HU	
SCP REVISION		

TITLE: PIPING AND INSTRUMENT DIAGRAM ALKYLATOR

SCALE: NONE
PROJECT NO.: 156217
CONTRACT NO. / WORK ORDER NO.: D-032-1225-001 / 0-3515-2
DWG. NO.: JCP-32-P1-EF-001
REV: 11

FILE NAME: JCP-32-P1-EF-001
2004 10:03:19 PM

E-3205
BENZENE COLUMN REBOILER

TEMA TYPE:	BEM	
SURFACE AREA:	961.1 m2	
DUTY:	14.80 Mkcal/hr	
	SHELL:	TUBE:
DESIGN P(kg/cm2g) AT T(C):	51.00/FV AT 426.0	7.50/FV AT 245.0
INSULATION TYPE AND THICK:	HC - 64 mm	HC - 64 mm
MATERIAL OF CONSTRUCTION:	CS	
TRIM:	XD1A	E

D-3209
BENZENE COLUMN REBOILER CONDENSATE POT

DIMENSION:	1000.0 mm ID X 3000.0 mm T-T
DESIGN P AND T:	51.00 kg/cm2g AND 426 C
MINIMUM P AT T:	/FVEXTERNAL AT 426 C
MATERIAL OF CONSTRUCTION:	CS
INSULATION TYPE AND THICK:	HC - 64 mm

C-3201
BENZENE COLUMN

DIMENSION:	3600.0 mm ID X 31900.0 mm T-T
DESIGN P AND T:	7.00 kg/cm2g AND 245 C
MINIMUM P AT T:	/FVEXTERNAL AT 245 C
TYPE AND MATL OF TRAY:	28MD+18ECMD - 410 S.S.
MATERIAL OF CONSTRUCTION:	CS
INSULATION TYPE AND THICK:	HC - 64 mm (SHELL) - (HEAD)

OFF SPEC 32-P1-EF-108 1314 E-3225 — HAP P-32177-4"-NBZ3-PP38-NT — NNF

SAMPLE LINE 1560 32-P1-EF-001 R-3201 — HAP P-32307-0.75"-NBZ3-HC38-ET

DEPRESSURE/PURGE 32-P1-EF-019 1205 E-3206 — HAP P-32099-8"-XD1JA-PP38-NT — 2 PHASE NNF

1404 32-P1-EF-001 LC-32001

ALKYLATOR BTMS 1189 32-P1-EF-001 R-3201 — HAP P-32027-10"-NBZ3-HC64-NT

SAMPLE EFFLUENT 1492 32-P1-EF-010 R-3202 — HAP P-32119-0.75"-XD1JA-N -NT

DETAIL "A" ESD-5, 32120 — XV 32043X SIS — FC TSO — DETAIL "A" ESD-5, 32120 — XV 32043Y SIS — FC TSO

FY 32001 / FV 32001 — FC 6" — 20"x6" — 2 PHASE — HAP P-32027-20"-NBZ3-HC64-NT

FE 32001 — 12"x10" — 0.5" — 12"x10"

XD1JA NBZ3 — 25 — 1"x0.75" — 1" — MIN

HAP P-32217-20"-EBZ-HC51-NT — NBZ3 EBZ — 24"x20" — 24"

C-3201
Trim: TR-32322-EBZ -HC
Trim: TR-32333-E HAP-HC

MD TRAYS

HAP P-32106-36"-E-HC64-NT — EBZ E — (DO NOT POCKET) — 36" — 2 PHASE

E-3205
Trim: TR-32039-XD1A -HC

HAP P-32105-30"-E-HC64-NT — 30"

HHLL=3150.0 mm
HLL=2850.0 mm
NLL=2150.0 mm
LLL=750.0 mm
LLLL=450.0 mm

BTL=9000MM — BTL= — 10" — 30"

HAP P-32846-12"-EBZ-HC38-ET — 3" — 30"

HAP P-32845-12"-EBZ-HC38-ET — HAP P-32844-12"-EBZ-HC38-ET

HAP V-32022-30"-EBZ-PP38-NT — FLARE 3206 32-P1-EF-112

V-32303-12"-EBZ-PP38-NT — PRD-32291 AT C-3204 — 10775 32-P1-EF-101 — 12"

V-32303-12"-EBZ-PP38-NT — PRD-32290 AT C-3204 — 10793 32-P1-EF-101 — 12"

V-32303-12"-EBZ-PP38-NT — PRD-32289 AT C-3204 — 10807 32-P1-EF-101 — 12"

V-32303-12"-EBZ-PP38-NT — PRD-32028 AT C-3204 — 10808 32-P1-EF-101 — 12"

HAP V-32111-2"-EBZ-N -NT — EBZ E — 2"x0.75" — FI 32311 — 1"x0.75" — PCV 32317 — PSET=1.00 kg/cm^2g — 1" — 2"x1"

PRD 32021D — PSET=7.00 kg/cm^2g 8T10 — 14"x10" — 12"x8" — HAP P-32502-12"-EBZ-HC38-ET

PRD 32021C — PSET=7.00 kg/cm^2g 8T10 — 14"x10" — 12"x8"

PRD 32021B — PSET=7.00 kg/cm^2g 8T10 — 14"x10" — 12"x8"

PRD 32021A — PSET=7.00 kg/cm^2g 8T10 — 14"x10" — 12"x8"

CSO — CSC — 12" — 14"

FG-32020-2"-E-N -NT — 32-P1-EF-112 | 10770

BENZENE COLUMN OVERHEAD PRESSURE CONTROL
OPEN / CLOSED — PV-32032 — PV-32025 — 0 — 50% — 100% — PC-32025A/B OUTPUT

PI 32029X / PI 32029Y / PI 32029Z — 2OO3 — ESD-5 32120 — PT 32029X / PT 32029Y / PT 32029Z — DETAIL "O2"

HAP P-32028-30"-EBZ-HC51-NT — (DO NOT POCKET) — OVHD 1201 32-P1-EF-019 — E-3206 TUBE SIDE

RTD — TW 32065 — TUT 32303 — TI 32065 — PT 32025 — DETAIL "O2"

BIAS — HC 32052 — PY 32025A — SP — PC 32025B — STEAM OUTLET 1249 32-P1-EF-019 — PC-32032

PC 32025A — VENT TO FLARE 1485 32-P1-EF-020A — PV-32025

PT 32027 / PI 32027 — IPL

HAP P-32163-8"-EBZ-HC38-NT — REFLUX 32-P1-EF-020A 1438 — P-3205A/B

TI 32093 / TW 32093 / TT 32093 — 36" MW — RTD — TW 32094 / TUT 32303 / TI 32094

PP 32058 — MIN

FC 32036 / FY 32036 / FV 32036 / FT 32036 / FE 32036 — 6"x3" — 3" — OFF-SPEC EB 33-P1-EF-128 2746 — P-3374

HAP P-33583-6"-EBZ-HC25-NT — HAP P-33176-6"-EBZ-HC25-NT — 8"x6" — 8"

TUI 32303 — TI 32243 — TUT 32303 — TW 32243 / TW 32062 — 24" MW — RTD

TC 32062 — TT 32062 — IPL — H — L

TI 32063 — TW 32063 — TUT 32303 — RTD

PDT 32028 / PDI 32028 — PT 32026 / PI 32026

VC-30 — LG 32017 — MAG — LT 32018 / LC 32018 — D/P — DC-30 EB/SM

TI 32064 — TW 32066 / TW 32064 — LG 32016 — MAG — UC — 2"

TO SAFE LOCATION — PSET=51.00 kg/cm^2g 1D2 — E — XD1A — PRD 32020 — 3"x2" — 2"x1" — 1.5" — GRADE

V-32353-3"-E-PP25-NT — SHS-32023-2"-XD1A-HC38-NT — PI 32241 — CSO

SHS-32006-3"-XD1A-HC38-NT — EQUALIZING LINE — 4"x3" — 1" — 10"x8" — 10"

SATURATED HP STEAM 1597 33-P1-EF-502 HEADER — SHS-32005-8"-XD1A-HC64.0 mm-NT

HP CONDENSATE 13856 33-P1-EF-506 — CH-32335-0.75"-XD1A-HC25-NT — SP — SP-32S08 — FE 32065 — T — 0.75" — 8" — 1"

FT 32065 — FV 32065 / FY 32065 — FC 6" — 8"x6" — DETAIL "A" ESD-5, 32120 — XV 32019X SIS — XV 32019Y SIS — FC TSO

CH-32005-8"-XD1A-HC51-NT — FREE DRAINING — 8"

D-3209
LLL=1350.0 mm
LLLL=400.0 mm
20" MW — TW 32115 — BTL=1600MM — 2" — 4" — 1"

ESD-5 32120 — LC 32017 — LT 32017 / LG 32015 — D/P — MAG

WAST WATER 9181 33-P1-EF-534 EB/SM SEWER — NNF — NC — 0.75" — HAP DH-32374-2"-E-N -NT

WASTE WATER 6721 33-P1-EF-534 EB/SM SEWER — DH-32373-2"-E-N -NT

CWR 3083 33-P1-EF-553 — CWR-32019-0.75"-A-N -NT

HS 32019C — ESD-5 32120 — HS 32019A

INTERLOCK DESCRIPTION
(FOR INTERLOCK DESCRIPTION SEE DWG. NO. JCP-32-P1-EF- 810)

HP CONDENSATE 1604 33-P1-EF-506 D-3311 — CH-32006-6"-XD1A-HC38-NT — 2 PHASE — CH-32323-4"-XD1A-HC38-NT

LV 32017 / LY 32017 — FC 3" — 6"x3" — 4"x3" — 2"

Trim: TR-32318-XD1A -HC

ESD-5 32120 — FC 32065 — SP — L

ESD-5 32120 — FC 32037 — SP — ESD-5 32201 — FT 32037 — FV 32037 / FY 32037 — FC 6" — 10"x6" — 14"x6" — 0.75" — SC-3-3204

HAP P-32093-10"-E-PP38-NT — NNF — 2 PHASE — OFF-SPEC EB 1320 32-P1-EF-108 E-3225

HAP P-32054-14"-E-HC64-NT — NC — 10"

HAP P-32173-14"-E-HC51-NT — CRUDE EB 1518 32-P1-EF-101 C-3204 — 2 PHASE

CWS-32019-0.75"-A-N -NT — CWS 3082 33-P1-EF-553

HAP P-32358-0.75"-E-HC38-NT

HAP P-32826-0.75"-E-HC38-NT

10. PIPING TO EXPAND IN A RANGE OF ORIFICE STRAIGHT LENGTH FOR UP AND DOWN STREAM.
11. DELETE.
12. PDI32028=PI32026-PI32027 (IPL)

NOTES
1. COMMON ALARM OF EACH HEAT TRACE LOCAL PANEL IS PROVIDED ON DCS.
2. DELETED.
3. HEIGHT BASED ON REBOILER HYDRAULICS AND TO PREVENT FLASHING IN FLOW ELEMENT.
4. DELETED
5. EQUALIZING LINE SIZED FOR FIRE RELIEF CONDITIONS.
6. DELETED.
7. WHERE REQUIRED, PIPING REMOVABLE SPOOLS SHALL BE PROVIDED TO ENABLE EXCHANGER HEADS REMOVAL.
8. ROUTE LEVEL BRIDLE DRAIN TO EB/SM SEWER AND VENT TO FLARE.
9. DELETED.
10. METERIAL OF 6" ELBOW UPGRADED TO A 234-WP-22-1 DURING T/A 2015 AGAINST MOC JCP-P-4164.

REV.	DATE	DESCRIPTION	DRAWN	CHKD.	APPD.	REFERENCE DRAWING
11	04.Sep.-2022	REVISED AS PER MOC-21-5695	MRH	CSK	GMM	FOR NEW JCP LEGEND AND SYMBOLS SEE DRAWINGS:
10	14.Apr.-2021	REVISED AS PER MOC JCP-P-9035	MRH	CSK	HBK	JCP-00-P1-EF-001 THRU JCP-00-P1-EF-039
09	24.Mar.-2021	REVISED AS PER MOC JCP-P-6993	MRH	CSK	MAT	FOR EXISTING SCP LEGEND AND SYMBOLS SEE DRAWINGS:
08	04.Apr.-2019	REVISED AS PER MOC JCP-P-5131	MRH	HAM	CHK	JCP-00-D-00-00001 THRU JCP-00-D-00-00023
07	01.Jan.-2017	REVISED AS PER MOC NO. JCP-P-5131	SPC	RAC	KMN	FOR EXISTING PORT LEGEND AND SYMBOLS SEE DRAWINGS:
06	08.Jul.-2016	REVISED AS PER MOC JCP-P-4164	CH	SHS	KMN	JCP-00-D-00-00001P THRU JCP-00-D-00-00012P

CONFIDENTIAL INFORMATION - REPRODUCTION AND USE PROHIBITED EXCEPT IN ACCORDANCE WITH COMPANY'S WRITTEN PERMISSION.

EPC CONTRACTOR: JGC
MANAGING CONTRACTOR: PARSONS E&C
JCP

	INITIAL	DATE
DRAWN	PEC	04.Feb.-2003
CHECKED		
CONTRACTOR APPROVAL	RRC	
JCP APPROVAL	JM, HU	
SCP REVISION		

TITLE: PIPING AND INSTRUMENT DIAGRAM BENZENE COLUMN

SCALE	PROJECT NO.	CONTRACT NO. / WORK ORDER NO.	DWG. NO.	REV
NONE	156217	D-032-1225-018	JCP-32-P1-EF-018	11

0-3515-2

FILE NAME : JCP-32-P1-EF-018

A1,841x594

27/2004 10:08:38 PM